

AMERICAN STANDARD
HEATING & AIR CONDITIONING

PLATINUM

MFR DATE
9/2021

MOD.NO. 4A7V0060A1000BE	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	27.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	40	40
HFC - 410A	12 LBS. 12 OZ.	OR 5.78 kg(SI)
10 °F	SC (TXV) OR SEE SH CHART IN LITERATURE	SCCR 5kA rms
Climatuff DuraTuff Spine Fin Quick - Sess		

AMERICAN STANDARD
HEATING & AIR CONDITIONING
Trane U.S. Inc.



CONDENSING UNIT

TYLER, TX 75707 ASSEMBLED IN USA

OUTDOOR USE

COMPR. MOT.	19.3 RLA	208/230 V	12.0 LRA
O.D MOT.	2.80 FLA	208/230 V	1/3 HP
DESIGN PSI - HIGH 480 LOW 480		F. ID. YNR	

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

C1



QR
CODE

BARCODE