

XB 14

MFR
DATE 2/2010

| | | |
|--------------------------------|-----------------------------|-----------------------|
| MOD.NO. 4TTB4030E1000AA | VOLTS | 208/230 |
| SERIAL NO. XXXXXXXXXX | PH 1 | HZ 60 |
| MINIMUM CIRCUIT AMPACITY | 12.0 | AMPS |
| OVERCURRENT PROTECTIVE DEVICE | USA | CANADA |
| MAX FUSE / BREAKER (HACR) | 20 | 20 |
| HFC - 410A | 7 LBS. 00 OZ. | OR 3.18 kg(SI) |
| 8 °F DESIGN SUBCOOLING | | |

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S. INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

OUTDOOR USE

| | | | | | |
|-------------------------------|-------------|-----|-------------------|-------------|-----|
| COMPR. MOT. | 9.1 | RLA | 200/230 V | 57.8 | LRA |
| O.D MOT. | 1.00 | FLA | 200/230 V | 1/5 | HP |
| M.E.A. NO. | | | F. ID. XXX | | |
| DESIGN PSI - HIGH 480 LOW 480 | | | | | |



BARCODE

**CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LABELED WITH ARI**