XL 14i

MFR
DATE 4/2007

MOD.NO. **4TTX4048B1000AA**		VOLTS	**208/230**
SERIAL NO. **XXXXXXXXX**	PH **1**	HZ	**60**
MINIMUM CIRCUIT AMPACITY		**27.0**	AMPS
OVERCURRENT PROTECTIVE DEVICE		USA	CANADA
MIN FUSE / BREAKER (HACR)		**40**	**40**
MAX FUSE / BREAKER (HACR)		**45**	**45**

HFC - 410A **7** LBS. **15** OZ. OR **3.60** kg(SI)

10 °F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick - Sess

AMERICAN STANDARD INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 ASSEMBLED IN USA

LISTED SECTION OF CENTRAL COOLING AIR CONDITIONER

OUTDOOR USE

COMPR. MOT.	**20.5**	RLA	**208/230**	V	**109**	LRA
O.D MOT.	**1.40**	FLA	**200/230**	V	**1/6**	HP

M.E.A. NO.

DESIGN PSI - HIGH 480 LOW 480

F. ID. **XXX**

ENERGY STAR

ARI PERFORMANCE CERTIFIED

ARI Standard 210/240 Unitary Heat Pumps

CERTIFICATION APPLIES ONLY WHEN THE COMPLETE SYSTEM IS LISTED WITH ARI

BARCODE

MILAN AC SUPPLY