

AIR CONDITIONER

MFR
DATE 2/2013

MOD.NO. 4TTB4042E1000BA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	23.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	40	40
HFC - 410A	8 LBS. 04 OZ.	OR 3.28 kg(SI)
8 +/- 3 °F DESIGN SUBCOOLING		
Climatuff DuraTuff Spine Fin Quick - Sess		

TRANE

A BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

3059934 OUTDOOR USE

COMPR. MOT.	17.9	RLA	208/230 V	112	LRA
O.D MOT.	0.93	FLA	200/230 V	1/5	HP
M.E.A. NO.	F. ID. XXX				
DESIGN PSI - HIGH 480 LOW 480					



AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

BARCODE

IR Ingersoll-Rand