

# XR 12

MFR  
DATE 07/2002

|                               |               |                |
|-------------------------------|---------------|----------------|
| MOD.NO. 2TTR2030A1000AA       | VOLTS         | 208/230        |
| SERIAL NO. XXXXXXXXX          | PH 1          | HZ 60          |
| MINIMUM CIRCUIT AMPACITY      | 18.0          | AMPS           |
| OVERCURRENT PROTECTIVE DEVICE | USA           | CANADA         |
| MIN FUSE / BREAKER (HACR)     | 30            | 30             |
| MAX FUSE / BREAKER (HACR)     | 30            | 30             |
| HCFC - 22                     | 4 LBS. 04 OZ. | OR 1.93 kg(SI) |

**BAYFCCV 065A** REQUIRED INDOORS FOR RATED PERFORMANCE

THE TRANE COMPANY  OUTDOOR USE

TYLER, TX 75711-9010 ASSEMBLED IN USA

|             |      |     |          |     |     |
|-------------|------|-----|----------|-----|-----|
| COMPR. MOT. | 13.5 | RLA | 208/230V | 73  | LRA |
| O.D MOT.    | .90  | FLA | 200/230V | 1/8 | HP  |
| M.E.A. NO.  |      |     | F. ID.   | XXX |     |

DESIGN PSI - HIGH 300 LOW 300

## BARCODE