

**TRANE XR**MFR 11/2020  
DATE

MOD. NO. 4TTR3060E1000NA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	27.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	45	45
HFC - 410A	7 LBS.	10 OZ. OR 3.46 kg(SI)

10 °F SC (TXV) OR SEE SH CHART IN LITERATURE      SCCR 5KA rm s  
 Climatuff DuraTuff Spine Fin Quick - Sess

**TRANE**CONDENSING UNIT  
SA11679Trane U.S Inc.  
TYLER, TX 75707

ASSEMBLED IN USA



OUTDOOR USE

COMPR. MOT.	20.8	RLA	208/230 V	127.1	LRA
O. D MOT.	0.93	FLA	200/230 V	1/5	HP
DESIGN PSI - HIGH 480 LOW 480			F. ID. V9R		

**AHRI CERTIFIED™**[www.ahridirectory.org](http://www.ahridirectory.org)Unitary Small AC  
AHRI Standard 210/240Certification applies only when the complete system  
is listed with AHRI.

BARCODE

QR  
CODE