

American Standard

MFR
DATE 12/2010

MOD.NO. 4A6C3042A3000BA	VOLTS	200/230
SERIAL NO. XXXXXXXXXX	PH 3	HZ 60
MINIMUM CIRCUIT AMPACITY	18.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	30	30
HFC - 410A 8 LBS. 03 OZ.	OR	3.72 kg(SI)
10 +/- 3° F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S. INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

OUTDOOR USE

COMPR. MOT.	13.5 RLA	208/230	V	88	LRA
O.D MOT.	1.30 FLA	200/230	V	1/4	HP
M.E.A. NO.		F. ID. XXX			
DESIGN PSI - HIGH 480 LOW 480					



ARI Standard 210/240
Unitary Heat Pumps

BARCODE

CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LABELED WITH ARI