

# ***XB 1000***

MFR  
DATE **06/98**

MOD.NO. <b>TTB036C100A0</b>	VOLTS	<b>200/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>1</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY	<b>22.0</b>	AMPS
<b>OVERCURRENT PROTECTIVE DEVICE</b>	USA	CANADA
RECOMMENDED FUSE / BREAKER (HACR)	<b>35</b>	<b>35</b>
MAX FUSE / BREAKER (HACR)	<b>35</b>	<b>35</b>
HCFC - 22 <b>6</b> LBS. <b>11</b> OZ.	OR	<b>3.03</b> kg(al)
BAYFCCV <b>071A</b>	REQUIRED INDOORS FOR RATED PERFORMANCE	

THE TRANE COMPANY  
TYLER, TX 75711-9010 MADE IN USA



OUTDOOR USE

COMPR. MOT. <b>16.0</b> RLA	<b>200/230</b> V	<b>88</b> LRA
O.D MOT. <b>1.30</b> FLA	<b>200/230</b> V	<b>1/4</b> HP
M.E.A. NO.		
DESIGN PSI - HIGH 300 LOW 300	F. ID. <b>L04</b>	