XL 15i

MFR
DATE 5/2011

MOD.NO. **4TTX5048A1000BA**		VOLTS	**208/230**
SERIAL NO. **XXXXXXXXX**		PH **1**	HZ **60**
MINIMUM CIRCUIT AMPACITY		**28.0**	AMPS
OVERCURRENT PROTECTIVE DEVICE		USA	CANADA
MAX FUSE / BREAKER (HACR)		**50**	**50**
HFC - 410A	**11** LBS. **00** OZ. OR		**4.99** kg(SI)

9 +/- 3°F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick-Sess

TRANE U.S. INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 **ASSEMBLED IN USA**

INTERTEK ETL LISTED C US

LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

3159934 OUTDOOR USE

COMPR. MOT.	**21.8**	RLA	**208/230** V	**117**	LRA
O.D MOT.	**0.93**	FLA	**200/230** V	**1/5**	HP
M.E.A. NO.			F. ID. **EXP**		

DESIGN PSI - HIGH 480 LOW 480

MILAD
HVAC SUPPLY CO.

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system is listed with AHRI.

B A R C O D E