

XL 13i

MFR
DATE 04/2002

| | | |
|--------------------------------|----------------------|-----------------------|
| MOD.NO. 4TWX3042A1000AA | VOLTS | 208/230 |
| SERIAL NO. XXXXXXXXXX | PH 1 | HZ 60 |
| MINIMUM CIRCUIT AMPACITY | 26.0 | AMPS |
| OVERCURRENT PROTECTIVE DEVICE | USA | CANADA |
| MIN FUSE / BREAKER (HACR) | 40 | 40 |
| MAX FUSE / BREAKER (HACR) | 45 | 45 |
| HCFC - 410A | 7 LBS. 05 OZ. | OR 3.32 kg(SI) |

BAYFCCV 069A REQUIRED INDOORS FOR RATED PERFORMANCE

THE TRANE COMPANY  OUTDOOR USE

TYLER, TX 75711-9010 ASSEMBLED IN USA

| | | | | | |
|-------------|-------------|-----|------------------|------------|-----|
| COMPR. MOT. | 19.2 | RLA | 208/230 V | 104 | LRA |
| O.D MOT. | 1.90 | FLA | 200/230 V | 1/4 | HP |
| M.E.A. NO. | | | F. ID. | W54 | |

DESIGN PSI - HIGH 480 LOW 480

BARCODE