

Allegiance 11

MFR
DATE 2/2005

MOD.NO. 2A7A1030A1000AA	VOLTS 200/230
SERIAL NO. XXXXXXXXXX	PH 1 HZ 60
MINIMUM CIRCUIT AMPACITY	17.0 AMPS
OVERCURRENT PROTECTIVE DEVICE	USA CANADA
MIN FUSE / BREAKER (HACR)	30 30
MAX FUSE / BREAKER (HACR)	30 30
HCFC - 22	4 LBS. 00 OZ. OR 1.81 kg(SI)
BAYFCCV 065A	REQUIRED INDOORS FOR RATED PERFORMANCE
Climatuff DuraTuff Spine Fin Quick - Sess	

AMERICAN STANDARD INC.



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER
23MF OUTDOOR USE

TYLER, TX 75707 **ASSEMBLED IN USA**

COMPR. MOT. 13.1 RLA	200/230 V	71 LRA
O.D MOT. .90 FLA	200/230 V	1/8 HP
M.E.A. NO.	F. ID. XXX	
DESIGN PSI - HIGH 300 LOW 300		



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI