

**TRANE****XR 15**MFR 7/2013
DATE

MOD.NO. 4TWR5049E1000BB	VOLTS 208/230
SERIAL NO. XXXXXXXXXX	PH 1 HZ 60
MINIMUM CIRCUIT AMPACITY 28.0	AMPS
OVERCURRENT PROTECTIVE DEVICE USA	CANADA
MAX FUSE / BREAKER (HACR) 50	50

HFC - **410A** **13** LBS. **10** OZ. OR **6.17** kg(SI)
8 +/- 3 °F DESIGN SUBCOOLING
 Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

TRANE

A BUSINESS OF INGERSOLL RAND
 TYLER, TX 75707 ASSEMBLED IN USA

LISTED SECTION OF
HEAT PUMP

3059934 OUTDOOR USE

COMPR. MOT. 21.8 RLA	208/230 V	117	LRA
O.D MOT. 1.00 FLA	208/230 V	1/5	HP
M.E.A. NO.	F. ID. XXX		
DESIGN PSI - HIGH 480 LOW 480			

**ENERGY STAR**

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
 AHRI Standard 210/240

Certification applies only when the complete system
 is listed with AHRI.

C**BARCODE** **Ingersoll-Rand**