

HEAT PUMP 13

MFR
DATE 5/2014

MOD. NO. 4TWB3024D1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH	1 HZ 60
MINIMUM CIRCUIT AMPACITY	17.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	25	25
HFC - 410A	5 LBS.	04 OZ. OR 2.35 kg(SI)

12 +/- 3 °F DESIGN SUBCOOLING
Climatuff Duratuff Spine Fin Quick-Sess Weathertron

Trane and American Standard



LISTED SECTION OF
HEAT PUMP

A BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA

3059934 OUTDOOR USE

COMPR. MOT. 12.8	RLA	208/230 V	59.1	LRA
O.D MOT. 0.77	FLA	200/230 V	1/8	HP
M.E.A. NO.		F. ID. KDQ		
DESIGN PSI - HIGH 480	LOW 480			

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

BARCODE

Ingersoll Rand