

American Standard

MFR
DATE 3/2011

MOD.NO. 4A7C3030A4000BA	VOLTS	460
SERIAL NO. XXXXXXXXXX	PH 3	HZ 60
MINIMUM CIRCUIT AMPACITY	5.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	15	15
HFC - 410A 5 LBS. 11 OZ.	OR	2.58 kg(SI)
10 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S. INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

OUTDOOR USE

COMPR. MOT.	3.7 RLA	460	V	28	LRA
O.D MOT.	.40 FLA	460	V	1/8	HP
M.E.A. NO.		F. ID.	XXX		
DESIGN PSI - HIGH 480 LOW 480					

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

BARCODE